#800 Series Jacket

0.020" HIGH IMPACT PVC

800 series jacket is made of white rigid PVC. It has a shiny, hard surface that resists accumulation of foreign material that may contaminate sanitary processes. The total thickness is 0.020 inches. It is washable and never needs painting. When installed correctly using Fastener Weld, 800 series jacket creates a hermetic seal that meets FDA and USDA standards.

Table 1: Jacket Technical Data

| Property | Test Method | Value |
|--------------------------------------|-------------|-----------------|
| Polyvinylchloride thickness [inches] | | 0.020 |
| Ambient temperature range | | 0°F to 140°F |
| Tensile strength [psi] | | 6500 |
| Cold crack temperature | | 0°F |
| Emissivity | | 0.91 |
| Perm Rating | | 0.031 perms |
| Fuel Contribution | ASTM E-84 | 0 |
| Flame spread / smoke development | ASTM E-84 | Less than 25/50 |

Standard roll is 50" wide and 100 yards long

Specifications are subject to change without notice. All statements and technical information contained herein are based on tests we believe to be reliable. The accuracy or completeness is not guaranteed under all circumstances. All flammability ratings and specifications are based on laboratory tests and do not describe the performance of these materials in a real life situation. Before using Accessible Products Company products, the user shall determine suitability for the intended use and user assumes all responsibility for improper selection.

